

PRODUCT CODE:

MOULDED PTFE ROD — VIRGIN

9120


COLOUR: WHITE

STANDARD LENGTH: 12"

STOCK NUMBER	DIAMETER INCHES	LBS./FT. APPROX.
9120 02000	2	3.50
9120 02250	2-1/4	4.40
9120 02500	2-1/2	5.40
9120 02750	2-3/4	6.40
9120 03000	3	7.50
9120 03250	3-1/4	8.75
9120 03500	3-1/2	10.00
9120 03750	3-3/4	11.50
9120 04000	4	12.95
9120 04250	4-1/4	14.50
9120 04500	4-1/2	16.15
9120 04750	4-3/4	17.19
9120 05000	5	20.70
9120 05500	5-1/2	23.75
9120 06000	6	29.15
9120 06500	6-1/2	32.75
9120 07000	7	40.35
9120 08000	8	51.78

PROPERTIES

- Outstanding chemical resistance.
- Excellent weatherability.
- Low coefficient of friction.
- Low dielectrical properties.
- Excellent heat and low temperature resistance.



TYPICAL APPLICATIONS

- Pump components
- Bushings
- Electrical parts
- Valve components
- Rings
- Seals

- Available from 1" to 20" diameter.
- Tolerance: Oversized, suitable to machine to dimension listed.



PRODUCT CODE:

MOULDED PTFE ROD — 25% GLASS-FILLED

9121


COLOUR: WHITE

STANDARD LENGTH: 12"

STOCK NUMBER	DIAMETER INCHES	LBS./SHEET APPROX.
9121 02000	2	2.94
9121 02250	2-1/4	4.53
9121 02500	2-1/2	5.56
9121 03000	3	6.59
9121 03500	3-1/2	9.33
9121 04000	4	13.34
9121 05000	5	21.32
9121 06000	6	30.02

PROPERTIES

- Similar to Virgin PTFE.
- Improved PV valve.
- Improved dimensional stability.
- Can be attacked by alkali.



TYPICAL APPLICATIONS

- Bushings
- Seals
- Wear parts
- Valve seats

- Available from 1" to 20" diameter.
- Tolerance: Oversized, suitable to finish to dimension listed.

