

PRODUCT CODE:


# NYLATRON GS® BUSHING STOCK

COLOUR: GREY STANDARD LENGTH: 8 FEET

STOCK NUMBER	O.D. INCHES	I.D. INCHES	LBS./FT. APPROX.
4170 0500 0375	1/2	3/8	0.054
4170 0625 0375	5/8	3/8	0.110
4170 0750 0500	3/4	1/2	0.138
4170 0875 0375	7/8	3/8	0.259
4170 0875 0625	7/8	5/8	0.167
4170 1000 0500	1	1/2	0.312
4170 1000 0750	1	3/4	0.195
4170 1250 0750	1-1/4	3/4	0.421
4170 1250 1000	1-1/4	1	0.255
4170 1500 1000	1-1/2	1	0.528
4170 1500 1250	1-1/2	1-1/4	0.313
4170 1750 1250	1-3/4	1-1/4	0.639
4170 1750 1500	1-3/4	1-1/2	0.374
4170 2000 1500	2	1-1/2	0.747

## PROPERTIES

- High wear and abrasion resistance.
- Low coefficient of friction.
- Ease of fabrication.
- Noise dampening characteristics.
- Non-abrasive to other materials.
- Able to operate with or without lubrication.
- Resilience and impact resistance.



## TYPICAL APPLICATIONS

- Bushings
- Bearings
- Sleeves
- Rollers

- Sold only in standard lengths.
- NYLATRON GS® is a general purpose, high strength 6/6 NYLON with MOLYBDENUM DISULPHIDE added to increase wear resistance. It is produced to meet federal specification LP-410A.
- Tolerances: O.D. 1/2" to 1"  $\pm 0.001$ "  
Over 1" to 1-1/2"  $+0.005/-0.000$ "  
Over 1-1/2" to 2"  $+0.010/-0.000$ "  
I.D. Supplied sufficiently undersize to finish to fractional ID listed.

NYLON 6/6 BUSHING STOCK available in standard and thick walls.

