

PRODUCT CODE:

CLEAR VINYL DOOR STRIP


2500

COLOUR: CLEAR

STOCK NUMBER	ROLL DIMENSIONS	WEIGHT LBS./ROLL	TYPE	AREA OF USE
2500 060	0.060" x 6" x 400'	62	CLEAR	INDOOR/OUTDOOR
2500 080	0.080" x 8" x 300'	100	CLEAR	INDOOR/OUTDOOR
2500 120	0.120" x 12" x 200'	150	CLEAR	INDOOR/OUTDOOR
2500 160	0.160" x 16" x 100'	133	CLEAR	INDOOR/OUTDOOR
2501 080	0.080" x 48" x 60'	120	CLEAR	INDOOR/OUTDOOR
2501 120	0.120" x 48" x 60'	180	CLEAR	INDOOR/OUTDOOR
2502 080	0.080" x 8" x 300'	100	CLEAR POLAR	INDOOR
2502 120	0.120" x 12" x 200'	150	CLEAR POLAR	INDOOR
2503 080	0.080" x 8" x 300'	100	CLEAR POLAR REINFORCED	INDOOR
2503 120	0.120" x 12" x 200'	150	CLEAR POLAR REINFORCED	INDOOR
2504 080	0.080" x 8" x 300'	100	GOLD WELD SCREEN	INDOOR
2504 120	0.120" x 12" x 200'	150	GOLD WELD SCREEN	INDOOR

PROPERTIES

- Optical clarity.
- Rounded edges.
- Concave/convex construction.
- Fire rated UL 94VO above 0.080" thickness.
- Resists conductance of heat and cold.
- Energy saving through reduction of air movement.



TYPICAL APPLICATIONS

- Strip doors
- Machine enclosures
- Flexible windows
- Noise abatement
- Dust barriers
- Clean room enclosures
- Welding screens

- Other widths, thicknesses, roll lengths and colours available.
- All clear door strip is USDA compliant for incidental contact with meat, poultry and dairy products.
- Operating temperature range — Standard: 0°F / 150°F.
Polar: -20°F / -140°F.
- Recommended size of strip to be used in the installation of doors:
Doors to 8 Ft high, use 8" strips,
Doors to 14 Ft high, use 12" strips,
Doors to 20 Ft high, use 16" strips,
Doors over 20 Ft high, use 16" reinforced strips.
- Overlap: generally two-thirds is sufficient. Noise control, full overlap is recommended.
- Also available — Safety strip: Bright orange to outline hazardous areas.
Weld screen: Gold colour protects against the incidental effects of ultra violet light in welding.
Ribbed surface: Triangular shape of ribbing helps prevent scratching from truck and cargo. Traffic reduced abrasion of strip rubbing against itself.



FLEXIBLE VINYL ROLLSTOCK

2510


COLOUR: CLEAR, POLISHED SURFACE

ROLL WIDTH: 54"

STOCK NUMBER	THICKNESS INCHES	ROLL LENGTH YARDS
2510 010	0.010	125
2510 016	0.016	75
2510 020	0.020	60

PROPERTIES

- Clear.
- Flexible.
- Excellent fire rating.



TYPICAL APPLICATIONS

- Signs
- Windows
- Luggage tags

